



Product identifier

RELATED CAS : 64742-47-8

EC Number : 926-141-6

EC Name : Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

REACH : 01-2119456620-43

Characteristics

MEASURE	UNIT	METHOD	TYPICAL VALUE
Density at 15°C	kg/m ³	ASTM D 4052	819.3
Appearance at 15°C	-	Visual	Clair & Limpide
Saybolt Colour	-	ASTM D 6045	-16.0
Pensky-Martens Flash Point	°C	ASTM D 93	75.0
Aromatic content	ppm	UV	223.1
Sulfur Content	ppm (m/m)	ASTM D 3120	0.1
Initial Boiling Point	°C	ASTM D 86	198.9
90% Distillation Point	°C	ASTM D 86	227.7
Dry Point	°C	ASTM D 86	237.1
Distillation range	°C	ASTM D 86	19.1
Pour Point	°C	ASTM D 97	-69.2
Kinematic viscosity at 40°C	mm ² /s	ASTM D 445	1.70
Benzene content	ppm	ASTM D 6229	0.0

Applications

- Heating

Additional information

Health, Safety & Environment

For safety information, please refer to the current safety data sheet, available at sdstotalsms.total.com.

Storage

Product must be stored under the conditions indicated on the current safety data sheet, in an unopened packaging, protected from light, moisture, dust and heat sources.

Warranty

TOTAL, TOTAL Fluides, their respective logos, and products or service names used herein are trademarks of TOTAL, unless indicated otherwise. This document may not be distributed, displayed, copied, or altered in whole or in part without TOTAL Fluides' prior written authorization.

Data provided in this document is issued in good faith to the best of our knowledge, according to analysis of representative samples and not on the actual product shipped or delivered. The information in this document relates only to the named product or materials when not in combination with other product or materials. We not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document.

The terms "we", "our", "TOTAL", and "TOTAL Fluides" are each used for convenience, and may include anyone or more affiliates of the TOTAL corporate group of companies.

Contact

EUROPE & AFRICA

Total Fluides
24, Cours Michelet
92069 Paris La Défense
France
Tel : + 33 1 41 35 40 00

AMERICAS

Total
Av. Winston Churchill
Santo Domingo
Republica Dominicana

Total USA
1201 Louisiana Street
Houston, TX 77002, USA
Tel: + 1 800-323-3198

ASIA PACIFIC & MIDDLE-EAST

Total Oil Asia-Pacific Pte
Ltd
182 Cecile Street
188720 Singapore
Singapore
Tel: + 65 68 79 22 00

Notes